Product Information

AVENO MBike 15W-40

0002-000710



ASTM D 2896:2021

Description

AVENO MBike 15W-40 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by high resilience and reliability and is specially designed for wet and oil-lubricated clutches. AVENO MBike 15W-40 has excellent lubricating film adhesion, good shearing stability, excellent cleaning properties and high aging resistance.

Instructions for use

Total Base Number (TBN)

AVENO MBike 15W-40 is suitable as motor oil for all motorcycles if the SAE 15W-40 specification is required.

7.1

Quality classification			
Specification			
• API SN		• JASO MA2	
Properties			
Excellent cold start properties		Outstanding shear stability	
High oxidation stability		 Very good detergent and dispersing properties 	
Prevention of black sludge formation		 Very good viscosity-temperature behaviorcatalyst suitability 	
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	107.1	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14.3	mm²/s	DIN 51659-2:2017-02
Viscosity Index	136		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	866	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-30	°C	ASTM D 7346:2015

mgkoh/g

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.