

Product Information

AVENO MBike 20W-50

0002-000712



Description

AVENO MBike 20W-50 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by a very high oxidation stability, excellent lubricating film adhesion and reliability under any load and is specially designed for wet and oil-lubricated clutches. AVENO MBike 20W-50 protects the engine from deposits and ensures a long service life.

Instructions for use

It is the ideal for 4-stroke engines. The formulation guarantees maximum protection for all engine components. It makes shifting gears easier and offers much smoother handling. The efficiency is reflected in the very low friction of engine components while maintaining maximum performance. It is ideally suited for road use.

Quality classification

Specification

- API SN
- JASO MA2

Properties

- Reduction of wear and tear
- Very stable viscosity index
- Rapid oiling of the engine
- Perfectly matched to road use
- Prevention of silting, varnishing, coking and corrosion
- Prevention of oil-related deposits in combustion chambers, in the piston ring zone and on the valves

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	161.5	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	17.9	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	123		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	874	kg/m ³	DIN EN ISO 12185:1997-11
Flash Point (COC)	266	celsius	DIN EN ISO 2592:2018-01
Total Base Number (TBN)	7.5	mgkoh/g	ASTM D 2896:2021