

# Product Information

## AVENO UTTO CVT

0002-000751



### Description

AVENO UTTO CVT is a multifunctional oil for agricultural, forestry and construction machinery. The recommended areas of application are gearboxes, hydraulic systems and wet brakes. AVENO UTTO CVT is specially developed for use in CVT transmissions and offers optimized friction behavior and maximum wear protection.

### Instructions for use

AVENO UTTO CVT ensures trouble free operation of all units under any application conditions and meets the regulations of many different manufacturers. AVENO UTTO CVT can not be used as engine oil.

### Quality classification

#### Specification

- API GL-4
- SAE 80W

#### Recommendation

- Allison C-4
- ARGO VT-DRIVE
- Case ICH CVXDrive
- Caterpillar TO-2
- CNH 410 B
- CNH MAT 3540, CNH MAT 3525, CNH MAT 3505
- CNH MS 1206, CNH MS 1207, CNH MS 1209
- Deutz-Fahr (SDF) T5400 CVT and T3500 CVT
- Eaton/Sperry Vickers I-280-S
- Eaton/Sperry Vickers M-2950-S
- Fendt Vario CVT Transmissions
- Ford ESN-M2C86-C, Ford ESN-M2C134-D
- John Deere J20 C (AutoPowr/eAutoPowr IVT Trans)
- Kubota UDT
- Massey Ferguson CMS M1141/M1143
- Massey Ferguson CMS M1145
- New Holland CVT
- Sauer Sunstrand/Danfoss (Hydrostatic trans fluid)
- Valtra G2-08
- VDS CVT Getriebe
- VOLVO WB 101
- ZF TE-ML 03E/06E/17E/05F/06F/21F/06K

### Properties

- High viscosity stability at all working temperatures
- Zinc-free formulation
- High flowability at low outside temperatures
- Oxidation stability and shear stability under difficult working conditions
- Excellent water tolerance in the hydraulic and transmission circuit

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	56.7	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	9.4	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	147		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -25°C	5930	mPa*s	ASTM D 5293:2020
Density at 15°C	866	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-42	°C	ASTM D 7346:2015