

Product Information

AVENO MBike 10W-50

0002-000809



Description

AVENO MBike 10W-50 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by a very high oxidation stability, excellent lubricating film adhesion and reliability under any load and is specially designed for wet and oil-lubricated clutches. AVENO MBike 10W-50 protects the engine from deposits and ensures a long service life.

Instructions for use

AVENO MBike 10W-50 is suitable as motor oil for all air- and water-cooled 4-stroke motorcycles if a viscosity of 10W-50 is required. The operating instructions of the engine manufacturer must be observed!

Quality classification

Specification

- API SN
- JASO MA2

Properties

- Very good shear stability
- Very good cold start properties
- Prevention of premature wear
- Tried and tested additives
- High safety reserves even under boundary lubrication conditions
- Optimum function of engine, clutch and transmission
- Very good resistance to oxidation and high temperature engine deposits

Technical specifications

| Properties | Data | Unit | Testing under |
|------------------------------|-------------|--------------------|--------------------------|
| Kinematic Viscosity at 40°C | 123.0 | mm ² /s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 17.8 | mm ² /s | DIN 51659-2:2017-02 |
| Viscosity Index | 160 | | DIN ISO 2909:2004-08 |
| Appearance | YELLOWBROWN | | VISUELL |
| Viscosity CCS at -25°C | 6700 | mpa*s | ASTM D 5293:2020 |
| Density at 15°C | 860 | kg/m ³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -39 | °C | ASTM D 7346:2015 |
| Total Base Number (TBN) | 7.6 | mgkoh/g | ASTM D 2896:2021 |