

# Product Information

## AVENO MBike 15W-50

0002-000811



### Description

AVENO MBike 15W-50 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by a very high oxidation stability, excellent lubricating film adhesion and reliability under any load and is specially designed for wet and oil-lubricated clutches. AVENO MBike 15W-50 protects the engine from deposits and ensures a long service life.

### Instructions for use

AVENO MBike 15W-50 is suitable as motor oil for all air- and water-cooled 4-stroke motorcycles if a viscosity of 15W-50 is required. The operating instructions of the engine manufacturer must be observed!

### Quality classification

#### Specification

- API SN
- JASO MA2

### Properties

- Very good shear stability
- Very good cold start properties
- Prevention of premature wear
- Tried and tested additives
- High safety reserves even under boundary lubrication conditions
- Optimum function of engine, clutch and transmission
- Very good resistance to oxidation and high temperature engine deposits

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	144.3	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	18.8	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	148		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	863.2	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015