

Product Information

AVENO MBike SAE 60

0002-000910



Description

AVENO MBike SAE 60 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by a very high oxidation stability, excellent lubricating film adhesion and reliability under any load and is specially designed for wet and oil-lubricated clutches. AVENO MBike SAE 60 protects the engine from deposits and ensures a long service life.

Instructions for use

AVENO MBike SAE 60 is suitable as motor oil for all air- and water-cooled 4-stroke motorcycles if a viscosity of SAE 60 is required. The operating instructions of the engine manufacturer must be observed!

Quality classification

Specification

- API SN
- JASO MA2

Properties

- Very good shear stability
- Very good cold start properties
- Prevention of premature wear
- Tried and tested additives
- High safety reserves even under boundary lubrication conditions
- Optimum function of engine, clutch and transmission
- Very good resistance to oxidation and high temperature engine deposits

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	165.7	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	23.5	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	173		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	857	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015
Total Base Number (TBN)	7.6	mgkoh/g	ASTM D 2896:2021