

# Product Information

## AVENO Prime PS 2010 0W-20

0002-001010



### Description

AVENO Prime PS 2010 0W-20 is a synthetic low-friction engine oil for gasoline and diesel engines with and without turbocharging and direct injection. AVENO Prime PS 2010 0W-20 is characterized by excellent cold-starting properties, minimized fuel consumption, friction and wear. Extended oil change intervals according to manufacturer's instructions.

### Instructions for use

AVENO Prime PS 2010 0W-20 is ideally suited for energy-saving, year-round use in modern passenger car petrol and diesel engines. It reduces CO<sup>2</sup> emissions and helps to protect the environment. AVENO Prime PS 2010 0W-20 is used in engines with the stated specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

### Quality classification

#### Specification

- ACEA C5
- ACEA C6
- API SP

#### Recommendation

- dexos<sup>®</sup>1 Gen 3
- MB 229.71
- Opel/Vauxhall OV 0401547 A-20
- PSA B71 2010
- Fiat 9.55535-CR1
- Ford WSS-M2C952-A1
- GM dexos D
- Renault RN17 FE
- STJLR.03.5006

### Properties

- Extremely stable and excellent viscosity behavior
- High shear stability
- Fuel economy under all operating conditions
- Very good detergent and dispersant properties
- Neutrality towards sealing materials
- Outstanding cold starting properties, even at low temperatures
- Low oil consumption due to low evaporation tendency
- Excellent protection against wear, corrosion and foaming
- Protection of natural resources through extended oil change intervals

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	43.2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	8.4	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	175		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	843	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-45	°C	ASTM D 7346:2015